



ISO 9001 : 2008

DATA SHEET

aquatreat®

AQUATREAT 559

DESCRIPTION:

- AQUATREAT 559 is an ultra high concentrated blend of strong dispersants and sequestrants that will avoid, reduce and even remove deposits of inorganic and organic nature such as calcium carbonate, calcium sulphate, magnesium hydroxide, silicates, mud, silt and microbiological fouling in Reverse Osmosis units.
- AQUATREAT 559 is food graded and can be used in the production of drinking water.

PROPERTIES:

- Appearance : light green liquid
- pH : 5,8 1,0
- Density : 1,17 ± 0,02
- Solubility in water : infinite

DOSAGE AND CONTROL:

- Dosage: Reverse osmosis/distillation units/scrubber: 3-15 ppm continuously on make-up water
- Control: A method to determine its concentration in the reject water is available.

PACKAGING:

- Polyethylene drums of 22 or 220 kilograms or containers of 1000 kilograms

HANDLING:

- Wear suitable protective clothing, gloves and eye-protection. For more information, kindly consult the material safety data sheet.

Exclusive distributor of Aquatreat in Vietnam:

WATERCHEM CORP.

No. 5, Alley 92, Nguyen Khanh Toan St, Quan Hoa Ward, Cau Giay Dist, Hanoi

Tel: (+84.4) 32 535 118 - Fax: (+84.4) 32 535 119

Email: chem@waterchemvn.com; Website: www.waterchemvn.com